


AD-A268 322



# Atlas of Formability

Aluminum 3004  
Flow Stress Curves



DTIC  
ELECTE  
AUG 18 1993  
S B D

DISTRIBUTION STATEMENT A  
Approved for public release  
Distribution Unlimited

93-18846



# NCEMT

93 8 16 02 5

**REPORT DOCUMENTATION PAGE**

Form Approved

OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>		<b>2. REPORT DATE</b> June 30, 1991	<b>3. REPORT TYPE AND DATES COVERED</b> Final March 31, 1991-June 30, 1991	
<b>4. TITLE AND SUBTITLE</b> Atlas of Formability Cast Aluminum 3004			<b>5. FUNDING NUMBERS</b>  C-N00140-88-C-RC21	
<b>6. AUTHOR(S)</b>  Howard A. Kuhn				
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> National Center for Excellence in Metalworking Technology (NCEMT) 1450 Scalp Avenue Johnstown, PA 15904			<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>	
<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b>  Naval Industrial Resources Support Activity Building 75-2, Naval Base Philadelphia, PA 19112-5078			<b>10. SPONSORING / MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b>				
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b>			<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b>  <p>In this investigation, flow behavior of Aluminum 3004 alloy was studied by conducting compression tests over a wide range of temperatures and strain rates. Stress-strain curves were recorded for each test condition. These data are essential in metalworking process design or finite element analysis of high temperature deformation.</p>				
<b>14. SUBJECT TERMS</b>  Aluminum 3004, High Temperature Deformation, Metalworking			<b>15. NUMBER OF PAGES</b> 22	
			<b>16. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b>  Unclassified	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b>  Unclassified	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b>  Unclassified	<b>20. LIMITATION OF ABSTRACT</b>	

**ATLAS OF FORMABILITY**

**ALUMINUM 3004**

**by**

**Howard A. Kuhn**

**National Center for Excellence in Metalworking Technology  
1450 Scalp Avenue  
Johnstown, PA 15904**

**for**

**Naval Industrial Resource Support Activity  
Building 75-2, Naval Base  
Philadelphia, PA 19112-5078**

**June 30, 1991**

**The views, opinions, and/or findings contained in this report are those of the authors and should not be construed as an official Department of the Navy position, policy, or decision, unless so designated by other documentation**

## TABLE OF CONTENTS

Testing Parameters . . . . .	1
Stress-Strain Curves . . . . .	2

ST #A, AUTH USNAVIRSA (MR PLONSKY 8/443-6684)  
 PER TELECON, 17 AUG 93 CB


DTIC QUALITY INSPECTED 3

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By <i>per telecon</i>	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

## Aluminum 3004

### Testing Parameters

Strain Rate (1/sec.)	Temperature (deg. F)	Graph Number	Page Number
0.05	482	AL05	2
0.05	653	AL14	3
0.05	900	AL08	4
0.05	Combination	AL20	5
0.1	527	AL11	6
0.1	816	AL12	7
0.1	Combination	AL21	8
1.0	482	AL15	9
1.0	653	AL19	10
1.0	900	AL16	11
1.0	Combination	AL22	12
6.6	527	AL09	13
6.6	826	AL10	14
6.6	Combination	AL23	15
15.0	482	AL02	16
15.0	653	AL13	17
15.0	900	AL03	18
15.0	Combination	AL24	19




**NCEMT**

GRAPH NO: AL14

TEMP: 653 F

STRAIN RATE: 0.05/SEC




**NCEMT**

GRAPH NO: AL08

TEMP: 900 F


STRAIN RATE: 0.05/SEC



**NCEMT**



GRAPH NO: AL20  
STRAIN RATE: 0.05/SEC




**NCEMT**

GRAPH NO: AL11

TEMP: 527 F

STRAIN RATE: 0.1/SEC




**NCEMT**

GRAPH NO: AL12

TEMP: 816 F


STRAIN RATE: 0.1/SEC



**NCEMT**


GRAPH NO: AL21

STRAIN RATE: 0.1/SEC




**NCEMT**

GRAPH NO: AL15  
TEMP: 482 F  
STRAIN RATE: 1.0/SEC




**NCEMT**

GRAPH NO: AL19  
TEMP: 653 F  
STRAIN RATE: 1.0/SEC




**NCEMT**




**NCEMT**

GRAPH NO: AL22  
STRAIN RATE: 1.0/SEC



**NCEMT**






**NCEMT**

GRAPH NO: AL10


TEMP: 826 F

STRAIN RATE: 6.6/SEC




**NCEMT**

GRAPH NO: AL23  
STRAIN RATE: 6.6/SEC



**NCEMT**




**NCEMT**

GRAPH NO: AL13

TEMP: 653 F

STRAIN RATE: 15.0/SEC




**NCEMT**

GRAPH NO: AL03


TEMP: 900 F

STRAIN RATE: 15.0/SEC



**NCEMT**

GRAPH NO: AL24  
STRAIN RATE: 15.0/SEC



**NCEMT**